

# SARSILMAZ




## SAR 762 MT-A

### MAKİNELİ TÜFEK / MACHINE GUN

#### TEKNİK VERİ (TECHNICAL DATA)

KALİBRE (CALIBER)	7.62 x 51 mm NATO
ÇALIŞMA SİSTEMİ (OPERATING PRINCIPLE)	GAZ TAHRİKLİ, MEKANİZMASI AÇIK POZİSYONLU (GAS OPERATED, OPEN BOLT)
BESLEME (AMMUNITION FEED)	MAYON (M13) (BELT FEED M13)
ATEŞLEME MODU (MODES OF FIRE)	EMNİYET, SERİ ATIŞ (SAFETY, FULL AUTO)
TETİK AĞIRLIĞI (TRIGGER PULL)	50-80 N
ATIM SAYISI (RATE OF FIRE)	1. KONUM 650-850 ATIM/DK. (650-850 RND/MIN AT 1. POS.) 2. ve 3. KONUM EN AZ 750 ATIM/DK. (min. 750 RND/MIN AT 2 and 3 POS.)
DAĞILIM (ACCURACY)	5 MOA
ETKİLİ MENZİL (EFFECTIVE RANGE)	1100 m
YİV-SET (RIFLING)	4 SAĞ 304,8 mm (4 RH 1:12")
NAMLU ÇIKIŞ HIZI (MUZZLE VELOCITY)	850 m/s (±15 m/s)

REV:0 - 15/10/2024



## EBATLAR (DIMENSIONS)

1- UZUNLUK (LENGTH)	1048 mm ( $\pm 10$ mm) 41.3"
2- NAMLU UZUNLUĐU (BARREL LENGTH)	670 mm ( $\pm 3$ mm) 26.3"
3- YÜKSEKLİK (HEIGHT)	230 mm 11" ( $\pm 10$ mm) 9.1"

## AĐIRLIKLAR (WEIGHTS)

AKSESUARSIZ AĐIRLIK (WITHOUT ACCESSORIES WEIGHT)	10800 g ( $\pm 150$ g) / 381.5 oz
--	-----------------------------------

## GENEL ÖZELLİKLERİ (GENERAL FEATURES)

- 3 KADEMELİ GAZ VALFİ (GAS VALVE 3 POSITIONS)
- OPSİYONEL ATIŞ MODLU TETİK (OPTIONAL SELECTABLE FIRE)
- HIZLI DEĐİŐTİRİLEBİLEN NAMLU (QCB)
- KOAKSİYEL BAĐLANTI (COAXIAL MOUNTED)
- PLATFORM KULLANIMI (PLATFORM USE)

REV:0 - 15/10/2024

SARSILMAZ SİLAH SANAYİ A.Ő.  
Düzce 1. Organize Sanayi Bölgesi  
5. Cadde No:12 Beyköy Beldesi  
Düzce / TÜRKİYE

TELEFON:  
+90 (380) 548 8011  
FAKS:  
+90 (380) 548 85 63

E-MAIL:  
sarsilmaz@sarsilmaz.com



sarsilmaz.com

